

MSDS

(Material Safety Data Sheet)

Chemical Name : PERESEAL[®] PC PAINTERS' CAULK MSDS No. : P 007
Date of Preparation : January 2014 Revision No. : #1

Section 1. Chemical Product and Company Identification

Product Name	: PERESEAL [®] Painters' Caulk	Emergency Telephone Number: +65 6558 6388
Supplier/Manufacturer	: PFE Technologies Pte Ltd	Telephone number for Information: +65 6558 6388
Address	: 9 Gul Street 4 Singapore 629238	
Email	: info@pfetec.sg	Fax Number: +65 6558 7310
Website	: www.pfetec.sg	

Section 2. Composition / Information on Ingredients

Hazardous Ingredients	CAS No. EINECS No.	Conc. %	Hazardous Symbol	Risks (R-phrases)
None	--	--	--	--

(1) For R-phrases in full: see heading 16

Section 3. Hazards Identification

- No hazard classification

Section 4. First-aid Measures

Eye Contact	:	Rinse immediately with plenty of water Seek medical advice
Skin Contact	:	Rinse immediately with plenty of water If irritation persists: seek medical advice
Inhalation	:	Remove the victim into fresh air Seek medical advice
Ingestion	:	Never give water to an unconscious person Do not induce vomiting Seek medical advice

Section 5. Fire-Fighting Measures

Extinguishing Media		
Suitable	:	All standard extinguishing media are suitable. This is a waterborne product and does not support combustion in the uncured state. The product does not contain combustible organic components which may yield smoke containing hazardous decomposition products.
Unsuitable	:	None

MSDS

(Material Safety Data Sheet)

Chemical Name : PERESEAL[®] PC PAINTERS' CAULK MSDS No. : P 007
Date of Preparation : January 2014 Revision No. : #1

Section 6. Accidental Release Measures

Personal Protection/Precaution : **See heading 8.1/8.3/10.3**
Environmental Precaution : Use appropriate containment to avoid environmental contaminant
Method of Cleaning up : Scrape up and place in a container fitted with lid. Label clearly with contents ready for disposal. Clean residues with water and detergents.

Section 7. Handling and Storage

Handling : Observe normal hygiene standards
Storage : Keep container tightly closed in cool, dry and ventilated area.
Storage Temperature : Room temperature
Quantity limit : N.D. kg
Storage life : 365 days
Materials for packaging
Suitable : synthetic material
Specific uses : **See information supplied by the manufacturer**

Section 8. Exposure Controls / Personal Protection

Exposure Limit Values

TLV-TWA	:	- mg/m ³	ppm
TLV-STEL	:	- mg/m ³	ppm
TLV-Ceiling	:	- mg/m ³	ppm
OES-LTEL	:	- mg/m ³	ppm
OES-STEL	:	- mg/m ³	ppm
MAK	:	- mg/m ³	ppm
TRK	:	- mg/m ³	ppm
MAC-TGG 8 h	:	- mg/m ³	
MAC-TGG 15 min.	:	- mg/m ³	
MAC-Ceiling	:	- mg/m ³	
VME-8 h	:	- mg/m ³	ppm
VLE-15 min.	:	- mg/m ³	ppm
GWBB-8 h	:	- mg/m ³	ppm
GWK-15 min.	:	- mg/m ³	ppm
Momentary value	:	- mg/m ³	ppm
EC	:	- mg/m ³	ppm
EC-STEL	:	- mg/m ³	ppm

MSDS

(Material Safety Data Sheet)

Chemical Name : PERESEAL[®] PC PAINTERS' CAULK MSDS No. : P 007
Date of Preparation : January 2014 Revision No. : #1

Exposure Controls

Occupational Exposure Controls : Use only in well-ventilated area
Environmental Exposure Controls : see Heading 13

Personal Protections

Respiratory Protection : Respiratory protection required in normal conditions of use
Hand Protections : Gloves
Eye Protections : Safety glasses
Skin Protection : Suitable protective clothing

Section 9. Physical and Chemical Properties

General Information

Appearance (at 20°C) : Paste
Odour : Characteristics
Colour : Variable in Color

Important Health, Safety and Environmental Information

pH value : N.D.
Boiling point/boiling range : N.D. °C
Flashpoint : N.D. °C
Explosion limits : N.D. Vol%
Vapour pressure (at 20°C) : N.D. hPa
Vapour pressure (at 50°C) : N.D. hPa
Relative density (at 20°C) : 1.5 g/cm³
Water solubility : Soluble
Soluble in : N.D.
Relative vapour density : N.D.
Viscosity (at 20°C) : N.D. Pa.s
Partition coefficient n-octanol/water : N.D.
Evaporation rate
ratio to butyl acetate : N.D.
ratio to ether : N.D.

Other Information

Melting point/melting range : N.D. °C
Auto-ignition point : N.D. °C
Saturation concentration : N.D. g/m³

Section 10. Stability and Reactivity

Conditions to Avoid/Reactivity : Stable under normal conditions
Materials to Avoid : None
Hazardous Decomposition Products : On burning: release of e.g. Carbon monoxide and Carbon dioxide

Chemical Name	: PERESEAL [®] PC PAINTERS' CAULK	MSDS No.	: P 007
Date of Preparation	: January 2014	Revision No.	: #1

Section 11. Toxicological Information

Acute Toxicity

LD50 oral rat	:	N.D.	mg/kg
LD50 dermal rabbit	:	N.D.	mg/kg
LD50 dermal rabbit	:	N.D.	mg/kg
LC50 inhalation rat	:	N.D.	mg/l/4h
LC50 inhalation rat	:	N.D.	ppm/4h

Chronic toxicity

	:	not listed
EC carc. cat.	:	not listed
EC muta. cat.	:	
EC repr. cat.	:	not listed

Carcinogenicity (TLV)	:	not listed
Carcinogenicity (MAC)	:	
Carcinogenicity (VME)	:	not listed
Carcinogenicity (GWBB)	:	not listed

Carcinogenicity (MAK)	:	not listed
Mutagenicity (MAK)	:	not listed
Teratogenicity (MAK)	:	not listed

IARC classification	:	not listed
----------------------------	---	------------

Routes of Exposure	:	Ingestion, inhalation, eye and skin
---------------------------	---	-------------------------------------

Acute Effects/Symptoms	:	Practically non-toxic
-------------------------------	---	-----------------------

Chronic Effects	:	None known
------------------------	---	------------

Section 12. Ecological Information

Ecotoxicity	:	No data available
Mobility	:	Volatile organic compounds (VOC): < 1% Insoluble in water For other physiochemical properties see HEADING 9

Persistence and Degradability

Biodegradation BOD₅	:	N.D.	%ThOD
Water	:	No data available	
Soil	:	T ½	N.D. days

Bioaccumulative Potential

:	log P _{ow}	N.D.
:	BCF	N.D.

Other Adverse Effects

:	WGK	1	
	Effects on the ozone layer		Not dangerous on ozone layer
	Greenhouse effect		No data available
	Effect on waste water purification		No data available

MSDS

(Material Safety Data Sheet)

Chemical Name : PERESEAL[®] PC PAINTERS' CAULK MSDS No. : P 007
Date of Preparation : January 2014 Revision No. : #1

Section 13. Disposal Considerations on Waste Materials

Disposal Methods : Recycle/reuse

Section 14. Transport Information

Classification of the substance in compliance with UN Recommendations

UN-number : --
CLASS : NOT SUBJECT
SUB RISKS :
PACKING :
PROPER SHIPPING NAME :

ADR (transport by road)

CLASS : NOT SUBJECT
PACKING :
DANGER LABEL TANKS :
DANGER LABEL PACKAGES :

RID (transport by rail)

CLASS : NOT SUBJECT
PACKING :
DANGER LABEL TANKS :
DANGER LABEL PACKAGES :

ADNR (transport by inland waterways)

CLASS : NOT SUBJECT
PACKING :
DANGER LABEL TANKS :
DANGER LABEL PACKAGES :

IMDG (maritime transport)

CLASS : NOT SUBJECT
SUB RISKS :
PACKING :
MFAG :
EMS :
MARINE POLLUTANT :

ICAO (air transport)

CLASS : NOT SUBJECT
SUB RISKS :
PACKING :
PACKING INSTRUCTIONS PASSENGER :

AIRCRAFT

PACKING INSTRUCTIONS CARGO AIRCRAFT :

Special precautions in connection with transport : not restricted for any mode of international transport

MSDS

(Material Safety Data Sheet)

Chemical Name	: PERESEAL [®] PC PAINTERS' CAULK	MSDS No.	: P 007
Date of Preparation	: January 2014	Revision No.	: #1

Section 15. Regulatory Information

Labeling not required according to available information

Section 16. Other Information

The information provided on this MSDS is correct to the best of our knowledge and information at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

N.A. = NOT APPLICABLE
N.D. = NOT DETERMINED
***** = INTERNAL CLASSIFICATION

Exposure limits:

TLV : Threshold Limit Value - ACGIH US 2000
OES : Occupational Exposure Standards - United Kingdom 1999
MEL : Maximum Exposure Limits - United Kingdom 1999
MAK : Maximale Arbeitsplatzkonzentrationen - Germany 2001
TRK : Technische Richtkonzentrationen - Germany 2001
MAC : Maximale aanvaarde concentratie - the Netherlands 2002
VME : Valeurs limites de Moyenne d'Exposition - France 1999
VLE : Valeurs limites d'Exposition à court terme - France 1999
GWBB : Grenswaarde beroepsmatige blootstelling - Belgium 1998
GWK : Grenswaarde kortstondige blootstelling - Belgium 1998
EC : Indicative occupational exposure limit values - directive 2000/39/EC

Chronic toxicity:

K : List of the carcinogenic substances and processes - the Netherlands 2002