



# PERESEAL

EXPERTISE IN SEALANT TECHNOLOGY

# PU

## HIGH PERFORMANCE POLYURETHANE SEALANT

**PERESEAL® PU** is a low-modulus elastic joint sealant that has excellent elasticity and possesses superb adhesion to all typical construction materials such as cement-based materials, concrete, brick, ceramic, glass, wood, iron, and plastics.



### APPLICATIONS

Sealing of expansion joints between pre-cast concrete panels, and between many construction materials. Also suitable for various bonding and sealing applications such as for window and door frames, prefab connection joints, roofing, and ducting.

- Possesses permanent elasticity
- Low modulus
- Non-sagging, no slump
- No surface tackiness after full cure
- No shrinkage
- Enhanced storage stability
- Paintable
- Cures bubble-free
- Easy application

**POLY-URETHANE**

**MOISTURE CURING**

UP TO  
**25%**  
MOVEMENT



## Low-modulus PU sealant with superb elasticity and adhesion for use in demanding sealing applications

### The Pereseal Difference



Home-grown brand with a focus on quality and control



Tested and certified for many quality standards



We have a wealth of experience in sealants and applications



Used for over 35 years in a wide range of projects



We take pride in our quality standards and control



With our experienced and knowledgeable team

www.pereseal.com

# PERESEAL

EXPERTISE IN SEALANT TECHNOLOGY

# PU

## HIGH PERFORMANCE POLYURETHANE SEALANT

### TECHNICAL DATA

Base	Polyurethane
Consistency	Thixotropic
Curing system	Moisture cure
Tack-free time (23°C / 50% R.H.)	30 - 60 minutes
Curing rate (23°C / 50% R.H.)	2.0 mm / 24 hours
Hardness	25 - 45 Shore A
Shrinkage	None
Specific gravity	1.20 - 1.25
Temperature resistance	-40°C to +70°C
Elastic recovery (ISO 7389)	≥ 70%
E100 Modulus (23°C) (ISO 8339)	0.30 - 0.35 N/mm <sup>2</sup>
Movement capability	±25%
Elongation at break (ISO 8339)	350%

### APPLICATION

Application method	Applicator gun
Application temperature	+5°C to +35°C
Clean	with white spirit before application
Tooling	with soapy solution before skin formation
Repair	with PERESEAL PU

### STANDARDS/APPROVALS

ASTM C920:2001	PSB Corporation
----------------	-----------------

### JOINT SIZE

Minimum width	10 mm
Maximum width	50 mm
Minimum depth	5 mm
Recommendation	joint width = 2 x joint depth

### SUBSTRATE

**Substrate:** All usual building surfaces

Surfaces should be clean, dry, free of dust and grease. We recommend a preliminary compatibility test before application.

### COLOUR AND PACKAGING

Colour	Concrete grey
Sausage volume	600 ml
Packaging	12 sausages / box

### OTHER NOTES

#### Storage and shelf life

12 months for unopened packaging in cool and dry storage place at temperature between 10°C to 25°C

#### Safety measures

Apply the usual industrial hygiene. Refer to the Material Safety Data Sheet of the product for other safety measures.

#### Remarks

Do not apply on frozen or wet surfaces or through standing water

*The directives contained in this documentation are the result of our experiments and of our experiences and have been submitted in good faith. Because of the diversity of materials and substrates and the great number of possible applications which are beyond our control, we cannot accept any responsibility for the results obtained. In every case, it is recommended to carry out preliminary experiments.*



Proudly distributed by PFE Technologies in Singapore

**PFE TECHNOLOGIES PTE LTD**  
9 GUL STREET 4 SINGAPORE 629238  
TEL: +65 6558 6388 | FAX: +65 6558 7310  
www.pfetec.sg

Sales enquiries: sales@pfetec.sg  
Technical enquiries: info@pfetec.sg

### ABOUT PFE

PFE Technologies Pte Ltd is an established distribution and manufacturing company producing and supplying abrasives and sealant products. The company has owned, manufactured, marketed and distributed the Pereseal range of sealants for over three decades.

Established in Singapore in 1978, PFE Technologies has gained a reputation for quality, reliability, and outstanding value. PFE's mission is to deliver a superior level of services and products to achieve enduring, life-long customer satisfaction and relationships.